



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-7521BU0225

Registration Number
Registriernummer

| | |
|---|---|
| Field of Application <i>Anwendungsbereich</i> | products of gas supply <i>Produkte der Gasversorgung</i> |
| Owner of Certificate <i>Zertifikatinhaber</i> | Recanati Europe S.r.l. Via Zona Industriale, 70, I-45010 Villadose (RO) |
| Distributor <i>Vertreiber</i> | Recanati Europe S.r.l. Via Zona Industriale, 70, I-45010 Villadose (RO) |
| Product Category <i>Produktart</i> | material transition fittings: transition on PE-HD for gas pipes (7521) |
| Product Description <i>Produktbezeichnung</i> | material transition fittings "G" made of metal for gas pipes made of PE 100 |
| Model <i>Modell</i> | Transition fitting |
| Test Reports <i>Prüfberichte</i> | laboratory control test: 1103755_001 from 11.03.2015 (TTR) |
| Test Basis <i>Prüfgrundlagen</i> | DVGW G 5600-1/(P) (01.10.2013) |

Date of Expiry / File No. 29.06.2020 / 16-0656-GNA
Ablaufdatum / Aktenzeichen

26.09.2016 Fi A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

| Type Typ | Technical Data Technische Daten | Remarks Bemerkungen |
|---------------------------|---|--|
| Transition fitting | nominal diameter: DN 25 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 32x3,0 mm |
| Transition fitting | nominal diameter: DN 40 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 50x4,6 mm |
| Transition fitting | nominal diameter: DN 50 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 63x5,8 mm |
| Transition fitting | nominal diameter: DN 80 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 90x8,2 mm |
| Transition fitting | nominal diameter: DN 100 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 110x10,0 mm |
| Transition fitting | nominal diameter: DN 125 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 125x11,4 mm |
| Transition fitting | nominal diameter: DN 150 max. operating pressure: 10 bar | dimensions plastic-sided (d x s): 160x14,6 mm |

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

connections: on the metal side welding shank according to DIN EN 12627, on the plastic side pipe nozzle PE 100